



5689 NW 35th Court, Miami, Florida 33142, USA
Tel:05-638-8810 Fax: 305-633-3840

PIPE CLEANER No. 7120



MADE IN U.S.A.

GENERAL DESCRIPTION:

Weld-All Pipe Cleaner No. 7120 is a special blend of solvents formulated to clean PVC, CPVC, ABS and Styrene Pipes & Fittings, all schedules and all diameters, prior to applying cement. This Pipe Cleaner will effectively remove oils, dirt, grease and other foreign matter from the surface of pipe and inside of fitting. It is very important the surface of pipe and inside of fitting is clean for a strong leak proof joint. This product is made in the U.S.A

APPLICATION:

Weld-All Pipe Cleaner may be used on PVC, CPVC, ABS and Styrene. Use applicator supplied with can or suitable applicator ½ the size of pipe being joined or clean cloth.

Application temperature: -10 degree F to 120 degree F
Storage temperature: -10 degree F to 110F degree F

PHYSICAL PROPERTIES:

Appearance: Liquid
Color: Clear
Shelf Life: Unlimited (Unopened can)

AVAILABILITY:

SIZE	PART NO	UNITS/CARTON		
4 Fluid Oz / 120ml	712004	24	Can with brush in cap	
8 Fluid Oz / 237ml	712008	24	Can with brush in cap	
16 Fluid Oz / 437ml	712016	12	Can with brush in cap	
32 Fluid Oz / 947ml	712032	12	Can with brush in cap	

DIRECTION FOR USE:

Keep container closed when not in use

1. Apply Cleaner with applicator supplied with can or suitable applicator or clean cloth
2. Wipe off with Clean Dry cloth
3. Apply cement according to instruction on cement can
4. Cement should not be applied when Cleaner is wet



5689 NW 35th Court, Miami, Florida 33142, USA
Tel:05-638-8810 Fax: 305-633-3840

PIPE CLEANER No. 7120



MADE IN U.S.A.

PRECAUTIONS:

EXTREMELY FLAMMABLE LIQUID, VAPOR MAY IRRITATE EYE OR SKIN, MAY CAUSE FLASH FIRE, MAY BE HARMFUL OR FATAL IF SWALLOWED. DO NOT USE NEAR HEAT, SPARKS AND FLAMES. KEEP OUT OF REACH OF CHILDREN

Ensure adequate ventilation to avoid vapor build up which may cause flash fire. Vapor build up may also cause dizziness, headache or eye watering. If symptoms are experienced use respiratory protection or leave area and provide more fresh air. Avoid contact with eyes, skin and clothing. Do not smoke and wear protective equipment while using

FIRST AID:

Inhalation: If breathing is difficult vacate to fresh air. If breathing problems persist seek immediate medical attention.

Eye Contact: Flush eyes thoroughly with water for 15 minutes. Seek immediate medical attention.

Ingestion: If swallowed, give 1-2 glasses of water immediately, call physician, hospital or poison control center immediately. **DO NOT INDUCE VOMITING**

SPILL: Remove all source of ignition and ventilate area. Soak up spill with absorbent material. Dispose of absorbent material in accordance with regulations. Personnel cleaning the spill should wear appropriate protective equipment.

WARRANTY: Weld-All™ warrants that all of its new products shall be of good quality and free from defects. If any product becomes defective Weld-All™ will replace defective product at no charge. **WARRANTY IS LIMITED TO REPLACEMENT OF DEFECTIVE MERCHANDISE**