



5689 NW 35th Court, Miami, Florida 33142, USA
 Tel: 305-638-8810 Fax: 305-633-3840

PRIMER - PURPLE
No. 8155



MADE IN U.S.A.

GENERAL DESCRIPTION:

Weld-All Primer No.8155 is a special blend of solvents formulated to quickly soften the joining surfaces of PVC and CPVC pipes and fittings. Use of primer ensures strong, leak proof joint. Use of Primer like an insurance policy against leaky joint. This product is made in the U.S.A

APPLICATION:

Weld-All Primer used with appropriate Weld –All Cement will make consistently strong, leak proof joint. It is important that the joining surfaces remain soft and wet prior to assembly- inserting pipe into the fitting. The main function of primer is to soften the surfaces of pipes and fittings prior to applying cement. Cement should be applied to joining surfaces while primer is still wet. Use of Primer is highly recommended for 3” and larger diameter pipes and fittings.

ALWAYS FOLLOW INSTRUCTION LISTED ON CEMENT CAN ON HOW TO APPLY PRIMER

Application temperature: -10 degree F to 120 degree F
 Storage temperature: -10 degree F to 110F degree F

PHYSICAL PROPERTIIES:

Appearance: Liquid
 Color: Clear OR Purple
 Shelf Life: Unlimited (Unopened can)

AVAILABILITY:

SIZE	PART NO	UNITS/CARTON		
4 Fluid Oz / 120ml	815104	24	Can with brush in cap	
8 Fluid Oz / 237ml	815108	24	Can with brush in cap	
16 Fluid Oz / 437ml	815116	12	Can with brush in cap	
32 Fluid Oz / 947ml	815132	12	Can with brush in cap	

DIRECTION FOR USE:

Keep container closed when not in use

1. Apply Primer inside of fitting and outside of pipe with applicator supplied with can or suitable applicator ½ the size of pipe diameter
2. Apply Cement while primer is still wet
3. Follow instruction listed on cement can on how apply cement



5689 NW 35th Court, Miami, Florida 33142, USA
Tel: 305-638-8810 Fax: 305-633-3840

PRIMER - PURPLE
No. 8155



MADE IN U.S.A.

PRECAUTIONS:

EXTREMELY FLAMMABLE LIQUID, VAPOR MAY IRRITATE EYE OR SKIN, MAY CAUSE FLASH FIRE, MAY BE HARMFUL OR FATAL IF SWALLOWED. DO NOT USE NEAR HEAT, SPARKS AND FLAMES. KEEP OUT OF REACH OF CHILDREN

Ensure adequate ventilation to avoid vapor build up which may cause flash fire. Vapor build up may also cause dizziness, headache or eye watering. If symptoms are experienced use respiratory protection or leave area and provide more fresh air. Avoid contact with eyes, skin and clothing. Do not smoke and wear protective equipment while using

FIRST AID:

Inhalation: If breathing is difficult vacate to fresh air. If breathing problems persist seek immediate medical attention.

Eye Contact: Flush eyes thoroughly with water for 15 minutes. Seek immediate medical attention.

Ingestion: If swallowed, give 1-2 glasses of water immediately, call physician, hospital or poison control center immediately. DO NOT INDUCE VOMITING

SPILL: Remove all source of ignition and ventilate area. Soak up spill with absorbent material. Dispose of absorbent material in accordance with regulations. Personnel cleaning the spill should wear appropriate protective equipment.

WARRANTY: Weld-All™ warrants that all of its new products shall be of good quality and free from defects. If any product becomes defective Weld-All™ will replace defective product at no charge. WARRANTY IS LIMITED TO REPLACEMENT OF DEFECTIVE MERCHANDISE